

**REQUEST FOR QUOTATION**

**Procurement of Medical Supplies and Equipment**

P.R. No./Date Received: **2020-08-0099/ 06 August 2020**

RFQ/P No. / Date: **2020-09-0102/ 03 September 2020**

The Philippine Competition Commission invites all eligible suppliers, contractors and consultants to quote the best offer for the described item in the attached **Technical Specifications** subject to the Terms and Conditions and within the **Approved Budget for the Contract (ABC)**.

**Required Documents/Information to be submitted as Attachments to the Quotation/Proposal:**

- **Mayor's/Business Permit**
- **PhilGEPS Registration Number**
- **Signed Specifications**

This pro-forma quotation maybe submitted through **registered** or **electronic mail** to the PCC Bids and Awards Committee (PBAC) Secretariat at above address or email to **npitalano@phcc.gov.ph** or **procurement@phc.gov.ph** on or before **08 September 2020, 12:00 NN** subject to the following **Terms and Conditions**:

1. All entries shall be typed or written in a clear legible manner.
2. No alternate quotation/offer is allowed, suppliers who submitted more than one quotation shall be automatically disqualified.
3. All prices offered herein are valid, binding and effective for THIRTY (30) calendar days upon issuance of this document. Alternative bids shall be rejected.
4. Price quotations to be denominated in Philippine Peso shall include all applicable government taxes subject to **(BIR 2306)** 5% R-VAT and **(BIR 2307)** 1% (PO) or 2% (JO) deductions.
5. PCC PBAC Technical Working Group may require you to submit documents that will prove your legal, financial and technical capability to undertake this contract.
6. Salient provisions of the IRR of RA 9184: Section 68 - Liquidated Damages and Section 69 - Imposition of Administrative Penalties shall be observed.
7. PCC reserves the right to reject any and all quotations, declare a failure, or not award the contract pursuant to Sec 41 of the same IRR.
8. In case of tie quotations, suppliers' presence are required during tie breaking through draw lots of toss coin.
9. In case supplier pro forma quotation is submitted, conditions will be governed by the submitted signed **Terms of Reference/Technical Specifications**.
10. Award will be made per item.

Very truly yours,

  
**JESON Q. DE LA TORRE**  
Head, PBAC Secretariat

Item	QTY	ABC	Technical Specifications	Brand/Model	Unit Price	Total Amount
(To be filled-up by the supplier)						
1	1	₱ 1,000.00	BP Apparatus (Sphygmomanometer)			
2	1	₱ 3,000.00	Stethoscope			
3	1	₱ 3,000.00	Bloog Glucose Monitor			
4	1	₱ 1,800.00	Pulse Oxymeter			
5	1	₱ 4,000.00	Nebulizer Machine			
6	2	₱ 1,400.00	Cervical Neck Collar			
7	3	₱ 300.00	CPR Face Shield Human Breathing Mask with One Way Valve			
8	2	₱ 200.00	Emergency Thermal Blanket			
9	3	₱ 1,800.00	Oils for Air Purifier and Humidifier (3-5 pcs set)			
10	3	₱ 210.00	PNSS 1000 ml			
11	4	₱ 320.00	Disposable Nebulizer Kit			
12	1	₱ 100.00	Height Measurement Chart (Adult)			
13	10	₱ 50.00	Syringe (5cc)			
14	10	₱ 80.00	Syringe (10cc)			
15	1	₱ 4,000.00	Wheelchair			
16	2	₱ 6,000.00	Folding Bed			
Total ABC		₱ 27,260.00		<b>TOTAL Amount</b>		
<b>Instructions:</b>			Please see attached Specifications for details.			

(Please provide **complete** information below)

We undertake, if our Proposal is accepted, to supply/deliver the goods in accordance with the specifications and/or delivery schedule.

We agree to abide by this proposal for the price validity period specified in the terms and conditions and it shall remain binding upon us and may be accepted at any time before the expiration of that period.

Until a Purchase/Job Order or a Contract is prepared and executed, this Quotation/Proposal shall be binding upon us. We understand that you are not bound to accept the lowest or any Proposal you may receive.

Signature over Printed Name : \_\_\_\_\_

Designation/Position : \_\_\_\_\_

Name of Company : \_\_\_\_\_

Address : \_\_\_\_\_

Telephone / Fax : \_\_\_\_\_

E-mail Address: \_\_\_\_\_

Company Tax Identification Number : \_\_\_\_\_

## 1. Aneroid Sphygmomanometer(BP Apparatus)



Lightweight and easy to carry

One-piece cuff made of durable synthetic fabric material

Stainless Steel Pressure Gauge Calibrate to 300 Hg

Flexible Single Lumen PVC Tubing

Adjustable Velcro Pressure Cuffs

Range: 0-300 mmHg

Accuracy: +/- 3 mmH

Calibrated at temperature range of 15 °C to 25 °C and a relative humidity range of 20% to 85%.

Should not leak air in excess of 4 mmHg/min (0.5kPa/min) when the valve is closed.

The maximum error of the measurement of the cuff pressure at any point of the scale range should be within  $\pm 3$  mmHg ( $\pm 0.4$  kPa).

## 2. Stethoscope



- Combination diaphragm/bell adult chestpiece precisely machined from aluminum alloy
- Ultra-lightweight, only 3.7 oz (105 g)
- Extra-large 1 3/8" diameter bell and highly sensitive 1 3/4" diaphragm
- ADC's AFD technology further enhances acoustic response; use light pressure for low frequencies, firm pressure for high frequencies
- Clinician headset boasts reinforcing yoke molded into the flexible 22" PVC tubing
- 15% thicker tubing (compared to Adscope 609), made without natural rubber latex or phthalates
- Overall length 30"
- 18 tubing colors and 4 satin metal finishes
- Adsoft™ Plus Snap-on silicone eartips
- Non-chill bell and diaphragm retaining rim for patient comfort
- Includes both large and small Adsoft™ Plus eartips and scope ID tag
- Individually acoustic tested

### 3. Blood Glucose Monitor



- Blood Glucose Meter

- Glucose Oxidase Enzyme
- Measurement Range 20-600mg/dl
- Result Calibration: Plasma-equivalent
- Battery Life: 1000 tests
- Lancing Device
- lancets
- Carrying case
- FREE test strips
- Pricker and lancets
- Get results in 4 seconds
- Smaller 0.4µL sample size. Alternate site testing
- Memory: Up to 300 records with date and time
- Meter Size: 85 x 40 x 16.4 mm
- Display Size: 35 mm x 32 mm
- Operating Temperature: 41-113°F (5-45 °C)
- Operating Relative Humidity: 10-90% (non-condensing)
- Hematocrit Range: 30 – 55%

#### 4. Pulse Oximeter



- Pulse oximeter - Battery life: lead acid battery; internal, rechargeable; fully charged in 6 hours.
- Approximately 4-5 hours of continuous use. Display & indications:
- SpO2: 3-digit LED (light-emitting diodes) display, 10.9mm high.
- Pulse rate: 3-digit LED display, 10.9mm high.
- Pulse strength logarithmically scaled, 8 segments remain.
- Low-battery LED flashes when approximately 30min of battery life remains.
- Sensors: All reusable LED flashes to alert the operator to check the sensor placement.
- SpO2: Range 0-100%
- Accuracy:  $\pm 2\%$  at 70-100%,  $\pm 3\%$  at 50-69%
- Averaging: 4.8- or 16-pulse beat average. - Pulse rate: Range 30-254bpm
- Accuracy:  $\pm 2\%$  at 30-254bpm –
- Averaging: 8 or 16-second average.
- Environmental specifications: Operating temperature 0 to 40°C.
- Storage Temperature: - 40 to 75°C.
- Relative humidity: 10-95%, storage (Non-condensing) 15-95%, operating.

## 5. Nebulizer Machine-4000



- Power: AC 220V/230V50 Hz
- Power Consumption: 180-220 VA
- Medication Capacity-5-10 ml
- MMAD 4 $\mu$ m
- Average nebulization rate: 0.2m/min-0.6m/min.
- Compressor Pressure Range: 30 to 36 Psi (210 to 250 Kpa/2.1 to 2.5 bar)
- Operating Pressure Range: 8-16 Psi (50-100 Kpa/0.5 to 1.0 bar)
- Flow range: 6-8 lpm
- Dimension( Lx W x H): 170.5x 148x86mm
- Weight: 1146g
- Standard Accessories: Adult mask, Child Mask, Nebulizer, Mouth piece, Air Tube, Filter

## 6. Cervical Neck Collar -

## Cervical Collar Traction

Neck Brace Support

Posture Corrector

Vertebra Protection



- Soft not Rigid Neck Brace
- Used for neck minor injuries like neck strains, sprains or whiplash problem
- Used to restrict excessive neck motion, but don't completely immobilize the neck.
- Made of High Density Foam with 100% Cotton Fabric cover.
- 3.5-inch Chin Height, also available in 3-inch and 4-inch
- Free size: Neck circumference 14"-18"

## 7. First Aid CPR Rescue Oxygen Inlet Face Shield Human Breathing Mask with one way valve



- 
- CPR pocket mask with O2O inlet. It can make patient breath fluently.
- Soft cushion
- Type: CPR Mask
- Material: ABS
- Features: Portable, First Aid Mask, Easy to Use
- Size: 12cm x 10cm x 2.6cm/4.72" x 3.94" x 1.02" (Approx.)
- Diameter: 2.6cm/1.02" (Approx.)

## 8. Emergency Thermal Blanket



- With special coating on the surface which can reflect the light back, so as to achieve the sunscreen effect
- Can also used as a insulation blanket in low temperature situation, a poncho in rainy weather, or a floor mat when sleeping
- Strongly reflective effect, easier for people to spot and carry out the rescue
- Light weight and can be folding, portable for carrying around

- Material: PET
- Size: 130 x 210 cm/51.18 x 82.68 inch
- Thickness: 12 UM
- Color: silver

### 9. Oils for Air Purifier and Humidifier



- 3-5pcs. 30-50ml aromatic oil for Air Purifier/Humidifier
- Scents: Lavander, Eucalyptus, Citrus

### 10. PNSS 1L



- PNSS 0.9 sodium chloride for injection 100ml (drip) or disinfectant



### 11. Disposable Nebulizer Kit



- 2.7 $\mu$  nebulizer with a low dead volume (0.7 cc)
- Leak-proof seal ensures efficient use of medication
- 10cc bowl with graduated volume markings
- 45-degree elbow
- Medication port directs medication to the nose

### 12. Height Measurement Chart (Adult)



### 13. Syringe(5cc)



- 5cc capacity
- Luer mount/luer lock with central nozzle 22x1", 0.70x25

### 14. Syringe(10cc)



- 10 ml capacity
- Luer mount/luer lock with central nozzle 22x1", 0.70x25

## 15. Wheel Chair



- 43 - 51 inches (1090 - 1295 mm).
- Lap height 27 inches (685 mm).
- Armrest height of the wheelchair is 30 inches (760 mm).
- Seat height of the wheelchair is shown as 19 inches (485 mm).
- Toe height is 8 inches (205 mm).
- The handle at the back of the wheelchair backrest is 36 inches (915 mm) high .
- width of the wheelchair measured to the outside of the rear wheels is 26 inches (660 mm).
- Length of the wheelchair is 42 inches (1065 mm) measured from the back of the rear wheels to the front of the footrests.
- An additional 6 inches (150 mm) is shown in front of the footrest for toe/foot space because the footrest only supports the heel and not the entire foot.
- The width between the footrests is shown as 18 inches (455 mm).

## 16. Folding Bed



- Size: 190cmx70cm
- Weight: Approx.18-23kg
- Material: Body/steel (powder coating)
- 100% Urethane polyester foam
- Normal Usage load: 150kg
- Backrest reclining gear type(flat)Maximum reclining angle 80-95 degrees

Prepared by:

  
RIMEL D. EVARISTO  
HRMO III, HCMD